



SPT70100TWDS-C fixture shown with SL9010-B and SL9010-R glass.

Catalog # _____

Type _____

Project _____

EXA TWIN

A two lamp wall sconce with lamp aiming adjustability. Wall or ceiling mount. Several glass diffusers available (sold separately) to compliment any decor. See attached "Exa Twin Glass Accessories" Spec Sheet.

Fixture is milled from solid brass and finished in hand-polished chrome, platinum or 24K polished gold plate.

Two different models available:

SPT: Built in Transformer

Canopy Dimensions: 1-3/16" (30mm) D x 4-3/4" (121mm) W

Mounting canopy with built-in, step down, dimmable 75W electronic transformer (120/12V LIGHTTECH LET-75) concealed in the wall mount assembly. This transformer incorporates electronic short circuit auto-reset, overload, and thermal protection.

SP: For Remote Transformer Use

Canopy Dimensions: 1" (25mm) D x 3" (76mm) W

Transformer not included.

Length from wall to end of fixture: 7-1/4" (184mm)

Distance between fixtures: 2-5/16" (59mm)

Lamp: Dependant on canopy selection:

SPT - (2) 35W max. MR16 FG GU5.3 base

SP - (2) 50W max MR16 FG GU5.3 base

Note: All open Sirius Lighting fixtures are required by UL to use Front Glass (lensed) MR lamps or low pressure, low voltage lamp types that are suitable for use without shielding (ANSI C78-260/UL2108). The individual lamp cartons must be suitably marked as low pressure and for open fixture luminaire useage.

Fixture is covered by one year replacement guarantee after date of purchase.

cULus listed. New York City Approved.

Example Order: -

Mounting

Fixture


Finish*

SPT- Mounting canopy with built-in step-down 75W electronic transformer.
1-3/16" (30mm) Deep x 4-3/4" (121mm) Wide.
(2) 35W max. MR16 FG lamps, GU5.3 base.

SP - Mounting canopy for remote power sources.
1" (25mm) Deep x 3" (76mm) Wide.
(2) 50W max. MR16 FG lamps, GU5.3 base.

70100TWDS

C - Polished Chrome
G - 24K Polished Gold
PL - Platinum



EXA TWIN GLASS ACCESSORIES

Catalog # _____

Type _____

Project _____



Spot Glass Diffuser

Height: 1-3/4" (44 mm)
Width: 2-1/4" (57 mm)

SL9010 - (B, BLK, F, G, LE, OR, R, S)
B (Satin Blue), BLK (Opaque Satin Black), F (Frosted), G (Green), LE (Lemon), OR (Orange), R (Red Satin), S (Opaque Silver Spot Glass)



Tulip

Height: 3-1/2" (89 mm)
Width: 3-1/8" (79 mm)

SL9006N - (A, CB, F, G, R, Y)
A (Antique Ivory Satin), CB (Cobalt Blue Satin), F (Frosted), G (Green Satin), R (Red Satin), Y (Yellow Satin)



Fluted Tulip

Height: 3-1/4" (83 mm)
Width: 3-1/8" (79 mm)

SL9016 - (CB, CC, F)
CB (Fluted Cobalt Blue), CC (Fluted Crystal Clear Glass), F (Fluted Frosted Glass)

*Also accepts 50W MR16 FG Lamp