


Single- and Two-Circuit Track Accessories


Specifications/Features

The track mounting accessories allow ConTech 1-Circuit and 2-Circuit track to be mounted with stems or cables to T-Bar ceilings, drywall or to junction boxes. ConTech recommends using a **minimum** of (2) mounting points for 2', 4' and 6' track sections, (3) mounting points for 8' sections and (4) mounting points for 12' sections of track.


Components are available in the following finishes: **B** (Black), **P** (White), **U** (Unfinished), **S** (Silver). Installations are suitable for dry locations only.




LA-1
 15/16" Grid Stud Type T-Bar Mounting Clip with #8-32 x 5/8" Long Studs. Finish: -P



LA-1A
 15/16" Grid Slide-On Style T-Bar Clip. Fits into channel in back of track. May be spaced to 4'. Finish: -S




LA-1C
 9/16" Grid T-Bar Clip with #8-32 x 5/8" Long studs. Finish: -P




LA-1CB SPACER
 Spacer for Deep Ceiling Tiles. Must be used with LA-1CB. Finish: -S

LA-1B
 15/16" Grid Deep Tile T-Bar Clip. Fits into channel in back of track. May be spaced to 4'. Finish: -S


LA-1CB
 9/16" Grid Deep Tile T-Bar Clip with #8-32 x 7/8" Long studs. Must be used with LA-1CB SPACER. Finish: -S




LA-11
 1-Circuit Replacement End Cap Supplied with track. Finish: -B, P, S



LA-16
 Grounded Outlet. Integral on/off switch, track polarity indicator. Max. 5 Amp capacity. Not UL Listed. Finish: -B, P



LA-117
 Planter or Utility Hook. Non-electrical, Not UL Listed. 10 lb. capacity. Finish: -B, P



LA-241
 Wireway Cover. For 2-Circuit T-Bar and Drywall Pendant Feed Kits. Use with LA-210 and LA-210A Live End Feeds. Finish: -B, P

LA-211
 2-Circuit Replacement End Cap Supplied with track. Finish: -B, P, S



8T FRT INSERT
 Decorative method of closing access to conductors. Required in lower installations. Can be field cut. Finish: -B, P, S




TA-4
 4' Plastic Cover For Track Raceway

TA-8
 8' Plastic Cover For Track Raceway For 1-Circuit track. Slides Into Back Of Track, Field Cuttable. Finish: -B




LA-50
 Swivel Stem Kit for Sloped Ceilings. Includes J-Box hardware, canopy cover, swivel adapter and mounting bracket for back of track. Less stem. Can be used for power feed. Finish: -B, P



LA-54
 Plastic Canopy with Set Screw. For use with LA-51, LA-5112 or LA-5118 to cover T-Bar attachment. Finish: -B, P


Continued on page 2

Single- and Two-Circuit Track Accessories




Cable Mounting Kit
Includes cable coupler (threaded for 1/4-20 stud), cable holder with lock nut, 1/16" galvanized cable, 1/4-20 hanger bolt and T-bar mounting clip with 1/4-20 stud.

- LAC-24** - 24" Steel Cable
- LAC-48** - 48" Steel Cable
- LAC-180** - 180" Steel Cable



Cable Mounting Kit with Toggle Bolt
For installation to dry wall ceiling. Includes cable coupler (threaded for 1/4-20 stud), cable holder with lock nut, 1/16" galvanized cable, 1/4-20 toggle bolt assembly and 1-7/8" diameter ceiling cover plate.

- LACD-24** - 24" Steel Cable
- LACD-48** - 48" Steel Cable
- LACD-180** - 180" Steel Cable




T-Bar Mount Feed Stem Kits
Allows mounting of track to 15/16" Wide T-Bar Grid. Includes canopy cover (4-3/4" dia.), T-Bar mounting assembly, mounting bracket for back of track. Can be used for power feed. Finish: -B, P

- LA-53** - Kit without Stem
- LA5312** - 12" Stem
- LA5318** - 18" Stem




T-Bar Mount Stem Support Kits
Allows stem mounting of track to T-Bar grid. Includes T-Bar clip, stem adapter, mounting bracket for back of track. Can not be used for power feed. Finish: -B, P

- LA-51** - Kit without Stem
- LA5112** - 12" Stem
- LA5118** - 18" Stem




Junction Box Mount Feed Stem Support Kits
Kit allows stem mounting of track to drywall ceilings. Includes J-Box hardware, canopy cover (4-3/4" dia.) and mounting bracket for back of track. Can be used for power feed. Finish: -B, P

- LA5012** - 12" Stem
- LA5018** - 18" Stem
- LA5018A** - Kit without Stem




Threaded Steel Pipe Stem with Coupling
Finish: -B, P, S

- 6" STEM**
- 12" STEM**
- 18" STEM**
- 24" STEM**
- 30" STEM**
- 36" STEM**
- 48" STEM**




Threaded Steel Pipe Stem without Coupling
Finish: -B, P, S

- 6" STEM(A)**
- 12" STEM(A)**
- 18" STEM(A)**
- 24" STEM(A)**
- 30" STEM(A)**
- 36" STEM(A)**
- 48" STEM(A)**




COUPLING
Coupling Only. For use with STEM series. Finish: -B, P




Threaded Rod Mounting Kit
Less rod (provided by others).
Finish: -B, P

- LA-52** - 5/16"
- LA-52-3/8** - 3/8"



LA2409
24" Wall Track Extension Bracket. Includes toggle bolt, washers and screws. 24" L x 1-3/4" W x 8-1/2" H. Finish: -B, P, S



LA3609
36" Wall Track Extension Bracket. Includes toggle bolt, washers and screws. 36" L x 1-3/4" W x 8-1/2" H. Finish: -B, P, S